



SPECIFICATIONS

MODEL		FC3JDPD	FC3JJPA	GD1JLPA	FG1JGPE	FG1JMPB
	Driving Position				RHD	
	Rear Tire				DUAL	
	G.V.M.R.(kg)	9,940		11,780	15,100	
	Type				Cab & Chassis	
	Seating Capacity				3	
DIMENSIONS	OAL (Overall Length) (mm)	5,760	7,490	8,190	6,395	8,680
	CH (Cab Height) (mm)	2,470		2,555	2,630	
	WB (Wheelbase) (mm)	3,180	4,350	4,850	3,780	5,050
	CW (Cab Width) (mm)				2,355	
	FH (Floor Height) (mm)	885		970	1,060	
	FOH (Front Overhang) (mm)	1,145		1,185	1,235	
	ROH (Rear Overhang) (mm)	1,350	1,910	2,060	1,285	2,300
ENGINE	Type				Direct Injection	
	Displacement cm ³	6,634		7,961		
	No. of valves per cylinder				4	
	Aspiration				Natural	
	Power Output kw @ r/min	115 / 2,900		150 / 2,900		
	Torque Nm @ r/min	443 / 1,500		546 / 1,500		
TRANSMISSION	Type	5 Speed M/T			6 Speed M/T	
	Ratio	1st 7.462 ~ 5th 1.000		1st 8.189 ~ 6th 1.000	1st 7.663 ~ 6th 1.000	
REAR AXLE	Type	Full Floating, single reduction, single speed				
	Ratio	5,142	4,625	4,875	5,857	5,428
SUSPENSION	Rear	Semi-elliptic main & aux. leaf				
	- Type	Reinforced				
	Front	Semi-elliptic w/shock abs.				
	- Type	Reinforced				
BRAKES	System	Air Over Hydraulic				
	Type: front & rear	Drum, Dual Circuit				
	Exhaust Brake	Electric-vacuum actuator w/valve in exhaust pipe				
WHEELS & TIRES	Wheels size	16x6.00-135		20x6.50-145	20x7.00-162	22.5x7.50-162
	Tire size	8.25R16-14PR		8.25R20-14PR	10.00R20-14PR	11R22.5
STEERING	Type	Recirculating ball with hydraulic booster				
FUEL TANK	Capacity Lts	100	200			
ELECTRICAL SYSTEM	System	24 Volts				
EXTERIOR	Fog Lamps	•				
	Under Mirror	•				
	Spare Tire / Spare Carrier	•				
INTERIOR	Audio (AM/FM)+ 2 Speakers	•				
	Air Conditioning / Heater	•				
	Sun Visor (Driver + Passenger)	•				
	Overhead Console	DR + Assist.		Driver Side Only		
OTHERS	Back buzzer	•				
	Tachometer with Overrun Buzzer	•				
	Fuel cap with key	•				

Sales Rep:

Contact Details:

Notes:

